



UNIVERSAL. FLAT. SPEEDY.

BLADE CULTIVATOR TAIFUN

The blade cultivator TAIFUN is a multi-purpose, highly efficient machine. It is a classic machine for seedbed preparation due to its high and spacious frame construction – especially for areas with catch crops and winter greening. The incorporation of liquid manure and organic fertilizer, as well as light and shallow stubble turning or second stubble cultivation and the combat of couch grass are ideal jobs for the TAIFUN.

Due to the ultra-flat cutting with duckfoot sweeps with a line spacing of 15 cm / 5.90", the TAIFUN blade cultivator is the perfect machine for a successful first mechanical weed control. The many possible combinations (e.g. shares, rollers, trailed weeder tines, support wheels, etc.) allow the blade cultivator to be optimally adapted to many different conditions.



Type/ Working width cm / ft.	No. of beams	Tines	No. of double drag tines	from HP/kW	Weight approx. kg / lbs
TAIFUN 250 / 8.20 ^{1,2)}	4	17	4	70/52	850 - 1130 kg 1874 - 2492 lbs
TAIFUN 300 / 9.80 ^{1,2)}	4	20	5	90/66	960 - 1250 kg 2117 - 2756 lbs
TAIFUN 400 / 13.10 ¹⁾	4	26	6	110/81	1530 - 1960 kg 3374 - 4322 lbs
TAIFUN 500 / 16.40 ¹⁾	4	34	8	130/95	1740 - 2260 kg 3857 - 4983 lbs
TAIFUN 600 / 19.70 ¹⁾	4	40	10	160/118	1880 - 2450 kg 4145 - 5402 lbs
TAIFUN 700 / 23.00 ¹⁾	4	46	12	190/140	2260 - 3000 kg 4983 - 6614 lbs

1) units optionally available with the following crumblers: F, R, FZ, RZ, RP47

2) rigid frame

STANDARD EQUIPMENT

- ✓ Large spring tines Vulcanus 50x13 with reversible share 53 mm
- ✓ Tine arrangement 4 rows
- ✓ Line spacing 15 cm
- ✓ Large frame dimension
- ✓ Lower links guided on both sides
- ✓ Lower and top link mountings are equipped with hardened bushings
- ✓ Spring-mounted double drag tines between the last tine row and the rear roller
- ✓ Parking position for double drag tines
- ✓ Crumblers parallelogram-guided and height-adjustable in the half breadboard
- ✓ Rear roller ball-bearing mounted

Choice of crumblers:

- » F: Flat rod crumbler ø 400 mm & following weeder tines 2 rows ø 10 mm
- » FZ: Flat rod crumbler ø 400 mm & serrated crumbler ø 320 mm & following weeder tines 2 rows ø 10 mm
- » R: Round rod crumbler ø 400 mm & following weeder tines 2 rows ø 10 mm
- » RZ: Round rod crumbler ø 400 mm & serrated crumbler ø 320 mm & following weeder tines 2 rows ø 10 mm
- » RP47: Ring packer roller ø 470 mm with spring stripper & following weeder tines 2 rows ø 10 mm

OPTIONS

- » Levelling plate
- » Side plate adjustable
- » HERKULES tine
- » Hydraulic working depth adjustment
- » Reinforcement spring of HERKULES tine
- » Duckfoot sweep 200/240 mm | 7.87/9.45"
- » Duckfoot share 220 mm | 8.66" made from carbide metal
- » Narrow share 53 mm | 2.08" made from carbide metal
- » Rubber support wheels integrated in the frame
- » Support wheels mounted in front of the side wings (only for TAIFUN 600 & 700)
- » Trailed weeder tines
- » Pneumatic seeder P-BOX
- » Warning signs with holder and LED-light



The allrounder for cutting the whole surface shallow.